

Rail Grips Installation Instructions

- Before installing, stretch the Rail Grip to make it more pliable
- Wet both the Rail Grip and the handrail with water
- Start 4" to 6" above the water's edge (always start from the bottom and work your way up)
- The Rail Grip must be a tight fit to reduce slipping
- A Tie" is provided to secure the zipper in place (optional)
- **Never** install the Rail Grip below the pool/spa water level
- Simply zip into place.. **Do Not use any tools** during installation to avoid cutting, or tearing the Rail Grip

Care/ Treatment:

- You may clean your Rail Grip every 3 – 6 weeks.
- Clean the Rail Grip with a mild soap (not detergent)
- Wash by hand, using warm water, scrub soiled areas, then rinse with cold water
- **Do Not Machine Wash/ Do Not use Dryer (air dry only)**
- Then reinstall your Rail Grip

The "Rail Grips" should have a snug fit. (Therefore will not slip on the rail...liability risk). The polyurethane material is the same material they use in "wet suits". It is highly "resilient". You simply wet the material and stretch it; then zip over the rail. The analogy is similar to that of stretching a balloon before you blow it up. If the person has already zipped the Rail Grip on the rail without stretching it, the zipper may pull apart. Remember, this is a fully resin (plastic) zipper. All you have to do is unzip the "Rail Grip". Wet the material, stretch and re-zip and it is as "Good as New". The zippers are double stitched along with a double sided tape for extra security. Therefore if a customer says the zipper pulled apart, it will most likely be from the grips in the zipper pulling apart and not a "tearing" of material.

We do have a 30 day policy and will be more than happy to return any defective product.

